

# SuperKlean™

Environmentally Exceptional Washdown Products

## Standard “Lite” Spray Nozzles

- Small, compact design.
- Durable rubber covers. Fully insulated.
- Perfect for applications where reduced size and/or flow rate are preferred.
- 3/8” female NPT inlet.

### 150LT

---

Inlet/Outlet Diameter: 3/8” NPT

---

Nozzle Body: Brass. Epoxy resin coated.

---

Cartridge: Stainless Steel

---

Weight: 1.05 lbs.

---

#### Recommended Operative Conditions

---

Maximum Pressure: 150 PSI

---

Maximum Temperature: 200 °F (93 °C)

---

Inlet Pressure (PSIG)	Flow Rate (GPM)
-----------------------	-----------------

---

25	4.00
----	------

---

50	6.25
----	------

---

75	7.75
----	------

---

100	9.00
-----	------

---

125	10.25
-----	-------

---

150	11.50
-----	-------



# SuperKlean™

Environmentally Exceptional Washdown Products

## Standard "Lite" Spray Nozzles

Part #	Description
1-LTB	Standard Nozzle body, brass one piece, epoxy resin coated
2-LTS	Standard Nozzle Lever, 304 stainless steel
3-LT	Lever bolt, bushing & nut, 304 stainless steel
4-LTDB	Nozzle cover, dark blue
4-LTW	Nozzle cover, white
5-LTS	Cage or "thrust collar," 304 stainless steel
6-LT	Lock screw or "end adapter," 304 stainless steel
7-LTS	Cartridge or "barrel assembly," 304 stainless steel, contains all working parts

