

SuperKlean™

Environmentally Exceptional Washdown Products

DuraFlow Spray Nozzles

- Front trigger guard cover designed to prevent accidental spray.
- Trigger lock mechanism built in.
- Quick connect receptacle for accessories.
- Compatible with DuraWand.

DH150S

Inlet/Outlet Diameter: ½" NPT

Nozzle Body: Stainless Steel. Epoxy resin coated.

Cartridge: Stainless Steel

Weight: 1.7 lbs

Recommended Operative Conditions

Maximum Pressure: 150 PSI

Maximum Temperature: 200 °F (93 °C)

Inlet Pressure (PSIG) Flow Rate (GPM)

High Flow

25	4.39
50	6.54
75	8.18
100	9.56
125	10.83
150	11.89

Low Flow*

25	2.93
50	3.86
75	4.91
100	5.78
125	6.71
150	7.19

*Low flow rates can be achieved with the purchase of flow restrictor adapter (Part: 8-FR-NPT)



SuperKlean™

Environmentally Exceptional Washdown Products

DuraFlow Spray Nozzles

Part #	Description
2-DHS	DuraFlow lever, stainless steel. Plastic dip
3-DH	DuraFlow nozzle lever bolt, stain- less steel
4-DHDB	Nozzle cover, dark blue
4-DHR	Nozzle cover, red
4-DHW	Nozzle cover, white
7-DHS	Cartridge or "barrel assembly", SS (contains all internal parts)(Dura- Flow nozzles)

2-DHS



7-DS



3-DH



4-DDB



4-DR



4-DW

