

# SuperKlean™

Environmentally Exceptional Washdown Products

## DuraFlow “Mini” Spray Nozzles

- Small, compact design.
- Fully insulated.
- 304 stainless steel construction.
- 1/2” female NPT inlet.

### DM150S

Inlet/Outlet Diameter: ½ ” NPT

Nozzle Body: Stainless Steel. Epoxy resin coated.

Cartridge: Stainless Steel

Weight: 1.25 lbs

#### Recommended Operative Conditions

Maximum Pressure: 150 PSI

Maximum Temperature: 200 °F (93 °C)

**Inlet Pressure (PSIG)    Flow Rate (GPM)**

#### High Flow

25	4.39
50	6.54
75	8.18
100	9.56
125	10.83
150	11.89

#### Low Flow\*

25	2.93
50	3.86
75	4.91
100	5.78
125	6.71
150	7.19

\*Low flow rates can be achieved with the purchase of flow restrictor adapter (Part: 8-FR-NPT)



# SuperKlean™

Environmentally Exceptional Washdown Products

## DuraFlow "Mini" Spray Nozzles

Part #	Description
2-DMS	DuraFlow "Mini" lever, stainless steel. Plastic dip
3-DM	DuraFlow "Mini" nozzle lever bolt, stainless steel
4-DMDB	Nozzle cover, dark blue
4-DMR	Nozzle cover, red
4-DMW	Nozzle cover, white
7-DMS	Cartridge or "barrel assembly," 304 stainless steel, contains all working parts

2-DMS



7-DMS



3-DM



4-DMDB



4-DMR



4-DMW

