

SuperKlean™

Environmentally Exceptional Washdown Products

DuraFlow “Mini” Spray Nozzles

- Small, compact design.
- Fully insulated.
- 304 stainless steel construction.
- 1/2” female NPT inlet.

DM150S

Inlet/Outlet Diameter: ½ ” NPT

Nozzle Body: Stainless Steel. Epoxy resin coated.

Cartridge: Stainless Steel

Weight: 1.25 lbs

Recommended Operative Conditions

Maximum Pressure: 150 PSI

Maximum Temperature: 200 °F (93 °C)

Inlet Pressure (PSIG) Flow Rate (GPM)

Standard Flow*

25	2.93
50	3.86
75	4.91
100	5.78
125	6.71
150	7.19

High Flow

25	4.39
50	6.54
75	8.18
100	9.56
125	10.83
150	11.89

*Standard flow rates can be achieved with the purchase of flow restrictor adapter (Part: 8-FR-NPT)



SuperKlean™

Environmentally Exceptional Washdown Products

DuraFlow "Mini" Spray Nozzles

Part #	Description
2-DMS	DuraFlow "Mini" lever, stainless steel. Plastic dip
3-DM	DuraFlow "Mini" nozzle lever bolt, stainless steel
4-DMDB	Nozzle cover, dark blue
4-DMR	Nozzle cover, red
4-DMW	Nozzle cover, white
7-DMS	Cartridge or "barrel assembly," 304 stainless steel, contains all working parts

