

SuperKlean™

Environmentally Exceptional Washdown Products

DuraSpray Spray Nozzles

- Designed for hanging hose applications (from the ceiling).
- Trigger lever to prevent accidental spraying.
- Quick connect receptacle for accessories.
- Compatible with DuraWand.

DS150S

Inlet/Outlet Diameter: ½" NPT

Nozzle Body: Stainless Steel. Epoxy resin coated.

Cartridge: Stainless Steel

Weight: 1.25 lbs

Recommended Operative Conditions

Maximum Pressure: 150 PSI

Maximum Temperature: 200 °F (93 °C)

| Inlet Pressure (PSIG) | Flow Rate (GPM) |
|-----------------------|-----------------|
|-----------------------|-----------------|

| High Flow | |
|-----------|--|
|-----------|--|

| | |
|----|------|
| 25 | 4.39 |
|----|------|

| | |
|----|------|
| 50 | 6.54 |
|----|------|

| | |
|----|------|
| 75 | 8.18 |
|----|------|

| | |
|-----|------|
| 100 | 9.56 |
|-----|------|

| | |
|-----|-------|
| 125 | 10.83 |
|-----|-------|

| | |
|-----|-------|
| 150 | 11.89 |
|-----|-------|

| Low Flow* | |
|-----------|--|
|-----------|--|

| | |
|----|------|
| 25 | 2.93 |
|----|------|

| | |
|----|------|
| 50 | 3.86 |
|----|------|

| | |
|----|------|
| 75 | 4.91 |
|----|------|

| | |
|-----|------|
| 100 | 5.78 |
|-----|------|

| | |
|-----|------|
| 125 | 6.71 |
|-----|------|

| | |
|-----|------|
| 150 | 7.19 |
|-----|------|

*Low flow rates can be achieved with the purchase of flow restrictor adapter (Part: 8-FR-NPT)



SuperKlean™

Environmentally Exceptional Washdown Products

DuraSpray Spray Nozzles

| Part # | Description |
|--------|---|
| 2-DSS | DuraSpray lever, stainless steel. Plastic dip |
| 3-DS | DuraSpray nozzle lever bolt, stain- less steel |
| 4-DSDB | Nylon cover, dark blue |
| 4-DSW | Nylon cover, white |
| 7-DSS | Cartridge or "barrel assembly," 304 stainless steel, contains all working parts |

2-DSS



7-DSS



3-DS



4-DSDB



4-DSW

